




Novoescocia® Plus Stainless steel



Profile with wide smoothed visible side made of AISI304 Stainless steel brushed finish. It has been designed to be placed in joints wall-floor, floor-floor or wall-ceiling, to make easier the cleaning and maintenance of corners. To be installed at the same time than flooring and wall tiling, it fits perfectly the installation. Ideal for public installations or homes.

General Features



Material:	Stainless steel AISI304
Length:	2,5 l.m.
Dimensions:	h: 10 mm. a: 37 mm.
Packaging:	10 u/box
Finishes:	Brushed stainless steel



Applications

Where to install Novoescocia® Plus Stainless steel:

- Corners between wall and kitchen countertops
- Perimeters in shower trays or bathtubs
- Wall-floor/wall-wall or wall-ceiling joints, horizontally and vertically

It's ideal for bathrooms, kitchens, medical consultations, restaurants, etc...

Its design is versatile and is appropriate for homes, offices, public buildings or installations with high requirements of hygiene and cleanliness.

Materials

Stainless steel

Novoescocia® Plus Stainless Steel is a profile made of stainless steel AISI-304. All material batches are tested with the composition test to determine that they fulfill with the specification of the alloy. Stainless steel used in the Emac® products has been also tested with salt spray test, exceeding 500 hours of exposition without signs of corrosion.

Stainless steel is a highly durable and resistant material, with an excellent superficial appearance that does not degrade along the time. Available in brushed finish. This finish is slightly porous and smooth, making easier the hygiene of the installation.

Technical features and tests



Alloy	AISI-304 Composition test of each batch		AIMME
Corrosion resistance	Salt spray test + 504 hours without change (stainless steel)	UNE 112017:92	AIMME

Installation

1. Before installing the flooring or the wall tiling, spread a layer of thin-set mortar on both surfaces where the profile will be installed
2. Place the profile aligning it with the wall and press it to make the thin-set mortar pass through the holes on the anchoring wing.
3. Then, place the tiles along the anchoring wings, pressing to get a perfect adhesion
4. Finally, clean the leftover material, remove the protective film and let dry

Cleaning and maintenance

The immediate cleaning of the material after its installation is necessary to avoid that remainings of mortar, concrete or iron particles from wool or tools could cause corrosion.

For indoor applications, you can use water with detergent or liquid soap to remove dirtiness and possible fingerprints marked on the surface. In high brightness finishes, you can use a glass cleaner. There are specific cleaners in the markets for stainless steel which clean the material and reduce possible stains. Whenever you clean stainless steel, ensure you rinse it well and dry totally to prevent fogging.

Steel wool or similar products, are not recommended because they could scratch the surface and create pitting corrosion. Pay special attention while using materials containing chlorides, they are not indicated because could oxidize the material. Hydrochloric acid or iron products in a long contact with the material are neither recommended. Do not use cleaners for common steel for the cleaning of stainless steel.

Technical information

You can find out more information about the technical features of Emac®'s products by downloading their Technical File from www.emac.es

If you have any query please contact our Technical Department in tecnico@emac.es