




Novobañera® 3



Novobañera® 3 is a profile made of PVC which makes an optimal sealing between the joint and the bathtub or counter top. This profile can be installed before the tiling work or once it is finished. It is available in white finish.

General features



Material:	PVC
Length:	1,5 - 2,5 m.l. (4ft9in - 8ft2in)
Dimensions:	a: 14 mm. (17/32")
Packaging:	100 u./box
Finishes:	01 - White

Applications

Where to install Novobañera® 3:

- Corners between wall and kitchen countertops.
- Perimeters in shower trays or bathtubs.
- Wall-floor/wall-wall or wall-ceiling joints, horizontally and vertically.

Technical Features and tests

Fire resistance	M2 (UNE 23-727-90)
Abrasion resistance	Very good
Working temperature	-10°C / 60°C
Resistance to chemical agents	Buena excepto con ácido crómico, sulfúrico y disolventes orgánicos como acetato y tolueno



AIM-PLAS

Materials



Novobañera® 3 is a profile made by coextrusion of PVC-P (rigid PVC) and PVC-U (flexible PVC). PVC-U provides a perfect adaptability to corners while PVC-P is suitable, due to its rigidity, to be the piece to be placed in the tiles as a support.

PVC (polyvinyl chloride), is a polar amorphous thermoplastic polymer highly resistant to abrasion, corrosion and a wide range of chemical products. Has a good resistance to impact, low water absorption, low electrical conductivity and is dimensionally stable.

Installation

Please, clean the surface destined to the installation of Novobañera® 3.

1. Cover generously the back face of Novobañera® 3 with an adhesive.
2. Fill also the posterior cavity with the same adhesive to ensure a perfect sealing and good grip.
3. Place the Novobañera® 3 on the corner and press firmly ensuring a good contact between both surfaces.
4. Finally clean the remaining material and let dry.

** In humid environments or in direct touch with water, it is recommended to seal the joints between Novobañera® with silicones.*

Cleaning and maintenance

The cleaning can be done with water and detergent or specific cleaner diluted. The correct use of bleach do not affect PVC.

It is not recommended using chromic acid, sulfuric acid or organic solvents as ethyl acetate, acetone or toluene.

Información técnica

Puede ampliar información sobre las características técnicas de los productos de Emac® descargando su ficha técnica en www.emac.es.

Para cualquier otra consulta adicional no dude en contactar con nuestro Departamento Técnico en tecnico@emac.es



Indoors



Wall tiling



Flooring



Recyclable