




## Novoescocia® 3



Novoescocia® 3 is a scotia profile with a high visible side, made by coextrusion of white color PVC. This solution avoids the accumulation of dirtiness in different encounters between wall-floor-ceiling, making the cleaning easy due to its rounded shape. Thanks to its features, it is suitable to be installed in places such as industrial kitchens, cold storages, communities, etc.

### General features



Material:	PVC
Length	2ft2in / 2,5 l.m.
Dimensions:	h: 1-15/32" / 37 mm. a: 2,36" / 60 mm.
Packaging:	15 u./box
Finishes:	01 - White



### Applications

Scope of Novoescocia® 3:

- Corners between walls and kitchen countertops
- Perimeters in shower trays or bathtubs.
- Encounters: wall-floor, wall-wall or wall-ceiling both horizontally and vertically.

It is an ideal product for bathrooms, kitchens, medical consultations, restaurants... It has a versatile design which is appropriate for homes, offices, public buildings or installations with high requirements of hygiene and cleaning such as garbage rooms, cold storages, communities, etc.

### Technical Features and tests

Fire resistance	M2 (UNE 23-727-90)
Abrasion resistance	Very good
Working temperature	-10°C / 60°C
Resistance to chemical agents	Buena excepto con ácido crómico, sulfúrico y disolventes orgánicos como acetato y tolueno



AIM-PLAS

### Materials

#### PVC

Novoescocia® 3 is a profile made by coextrusion of PVC-P (rigid PVC) and PVC-U (flexible PVC). PVC-U provides a perfect adaptability to corners while PVC-P is suitable, due to its rigidity, to be the piece to be placed in the tiles as a support.


PVC (polyvinyl chloride), is a polar amorphous thermoplastic polymer highly resistant to abrasion, corrosion and a wide range of chemical products. Has a good resistance to impact, low water absorption, low electrical conductivity and is dimensionally stable.

\*Find out more information by consulting the Technical Files of materials in [www.emac.es](http://www.emac.es)

### Installation

Clean the surface where Novoescocia® 3 PVC is going to be installed:

1. Apply a big amount of adhesive on the rear surfaces of the rigid piece of Novoescocia® 3. You can use an adhesive type silicone like.
2. Place the rigid piece on the encounter between wall and bathtub (or the encounter you need) and press, so both faces to join will make perfect contact with the surface. Then, let dry.
3. Once it is dry, join the flexible piece to the rigid one by introducing the toothed part in the hollow of the rigid one, as it is shown in the draw below. Then, press until the scotia is fixed and correctly installed.



\*If you need a perfect sealing, it is recommended applying silicone on the rear part of the sides of the flexible piece.

### Cleaning and maintenance

The cleaning can be done with water and detergent or specific cleaner diluted. The correct use of bleach do not affect PVC.

It is not recommended using chromic acid, sulfuric acid or organic solvents as ethyl acetate, acetone or toluene.

### Technical information

You can find out more information about the technical features of Emac®'s products by downloading its Technical File in [www.emac.es](http://www.emac.es).

If you have any query, please contact our Technical Department in [tecnico@emac.es](mailto:tecnico@emac.es).



Outdoors



Indoors



Wall tiling



Floorings



Recyclable